



1023

PARAMO a.s., Přerovská 560, 530 06 Pardubice
Czech republic

10

1023-CPD-0246F

EN 15322

Cut-back LIQUAFALT AR-RT 50A (Fm 2 B 6)

Initial cut-back

- Viscosity (efflux time C4).....Class 2 (100 – 200)
- Adhesivity (with granodiorite) in presence of water.... Class 3 (≥ 90)
- Setting ability - Distillation
 - Total distillate at 360 °C Class 7 (< 32)
 - % of total distillate fraction at 190 °C Class 5 (> 20)
 - % of total distillate fraction at 225 °C Class 6 (> 55)
 - % of total distillate fraction at 260 °C Class 5 (> 55)
 - % of total distillate fraction at 315 °C Class 5 (> 85)

Stabilised binder (EN 13074-1, EN 13074-2)

- Consistency at intermediate service temperature – Penetration
Class 4 (< 150)
- Consistency at elevated service temperature – Softening point
Class 4 (> 43)
- Cohesion Class 0

Aged binder (EN 13074-1, EN 13074-2, EN 14769)

- Durability of consistency at intermediate service temperature –
Class 2 (DV)
Penetration/25 = 59
- Durability of consistency at elevated service temperature –
Class 2 (DV)
Softening point = 53
- Durability of cohesion Class 0
- Dangerous substances NPD